

DRY ICE PRODUCTION + BLASTING

COMBI 350H



SYSTEM FEATURES

A pelletizer unit δ two dry ice blasting units

Stainless Steel Enclosure Moisture-Free & Noise-Reducing

Sub-Cooling Technology 2.2 LCO2 Conversion Factor

Closed Chamber Quick Start < 1 minute

Cold Jet. CONNECT™

RATED OUTPUT

Up to 772 lb/hr (350 kg/hr) of high quality dry ice pellets

DRY ICE PARTICLE SIZE

3mm pellets

HMI DISPLAY

15" Color Touch Screen

NOISE LEVEL

Below 75 db(A)

INLET LIQUID CO2 PRESSURE

232 - 319 psi (16-22 bar)

COMPRESSED AIR SUPPLY

72 - 232 psi (5-16 bar)

AIR QUALITY

ISO 8573-1, Min Class 3

NOZZLE AIR CONSUMPTION

106 - 388 cfm (3-11 m³/min) depending on nozzle combination

COMPRESSED AIR CONNECTION

1" claw coupling

MACHINE DIMENSIONS

Length x Width x Height: 101 in (256 cm) x 39 in (100 cm) x 74in (188 cm) Weight: 3,728 lb (1,691 kg)*

* Includes hydraulic oil

POWER SUPPLY

3 x 480 V+GR, 60Hz (3 x 400 V AC / 50Hz)

Imax: 25A

Solidly Grounded Wye Source

(TN-S Earthing System)

RATED POWER

15 Hp (11 kW)

Compliant with the EU Machinery Directive (CE) and UL Design Standards

